### This Page Is Inserted by IFW Operations and is not a part of the Official Record

#### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

#### IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



(11) Publication number:

06037837 A

# PATENT ABSTRACTS OF JAPAN Generated Document.

(21) Application number: 04187738

(51) Intl. Cl.: H04L 27/36

(22) Application date: 15.07.92

(30) Priority:

(43) Date of application publication:

10.02.94

(84) Designated contracting states:

(71) Applicant: NEC CORP

(72) Inventor: YASUSE ATSUSHI

(74) Representative:

## AMPLITUDE MODULATOR (54) MULTILEVEL QUADRATURE

(57) Abstract:

high quality by compensating surely PURPOSE: To provide a multilevel quadrature amplitude modulator of which is caused by the temperature the fluctuation of the output level change of a D/A converter.

converters 1 and 2 receive the digital signals D11, D12, D21 and D22 and CONSTITUTION: The D/A

Then, the voltage generating parts 62 and 72 generates the voltage Vc1 and amplifiers 3 and 4 receive the signals Vc2 so as to set the difference of the quadruple amplitude. The differential and 7 calculate the average levels of B1 and B2 and transmits them as the smoothed base band signals B1p and control voltage generating circuits 6 signals B2p and B2n of the negative phases respectively. Meanwhile, the and Vc2. A multiplier 5 receives the response to the control voltage Vc1 modulated signal Sm. The average the signals B1p-B2n respectively. calculating parts 61 and 71 of the signals B1p-B2n and produces a multilevel quadrature amplitude convert them into the base band Bln of positive phases and the output levels are controlled in signals B1 and B2 having the average levels at zero.

COPYRIGHT: (C)1994,JPO&Japio

4/24/2001

